

A.Kh. Attaev*

*Institute of Applied Mathematics and Automation KBSC RAS, Nalchik, Russia
(E-mail: attaev.anatoly@yandex.ru)*

Boundary control problem for a hyperbolic equation loaded along one of its characteristics

This paper investigates the unique solvability of the boundary control problem for a one-dimensional wave equation loaded along one of its characteristic curves in terms of a regular solution. The solution method is based on an analogue of the d'Alembert formula constructed for this equation. We point out that the domain of definition for the solution of DE, when the initial and final Cauchy data given on intervals of the same length is a square. The side of the square is equal to the interval length. The boundary controls are established by the components of an analogue of the d'Alembert formula, which, in turn, are uniquely established by the initial and final Cauchy data. It should be noted that the normalized distribution and centering are employed in the final formulas of sought boundary controls, which is not typical for initial and boundary value problems initiated by equations of hyperbolic type.

Keywords: hyperbolic equation, distributed oscillatory system, damping problem, gas/liquid flows, loaded equation, initial conditions, boundary conditions, analogue of the d'Alembert formula, boundary controls, normal distribution, distribution function.

Introduction

Let an oscillatory system be described by equation

$$u_{xx} - u_{tt} = \lambda u \left(\frac{x+t}{2}, \frac{x-t}{2} \right) \quad (1)$$

with the following initial and boundary conditions

$$u(x, 0) = \varphi_0(x), \quad u_t(x, 0) = \psi_0(x), \quad 0 \leq x \leq l, \quad (2)$$

$$u(0, t) = \mu(t), \quad u(l, t) = \nu(t), \quad 0 \leq t \leq T, \quad (3)$$

where λ is an arbitrary real number.

The boundary control problem involves searching admissible boundary values $\mu(t)$ and $\nu(t)$, that in a minimum time interval move the oscillatory system from the initial (2) to a predetermined final phase

$$u(x, T) = \varphi_1(x), \quad u_t(x, T) = \psi_1(x), \quad 0 \leq x \leq l. \quad (4)$$

Control (1) belongs to the class of loaded differential equations [1]. The point $\left(\frac{x_0+t_0}{2}, \frac{x_0-t_0}{2}\right)$ lies on the characteristic curve $x - y = 0$ of equation (1), for an arbitrary point $(x_0, t_0) \in \mathbb{R}^2$. The point (x_0, t_0) also moves to the point $\left(\frac{x_0+t_0}{2}, \frac{x_0-t_0}{2}\right)$ along the characteristic curve $x + y = x_0 + y_0$ of (1). The boundary control problem for the equation (1) with the right-hand side of the form $\lambda u_{tt}(x_0, t)$, which, according to [2], is called an essentially loaded equation, was studied in [3], [4]. Boundary value problems for hyperbolic equations with a load along one of the characteristic curves are studied in [5], [6]. For $\lambda = 0$, the formulated problem is fully investigated in [7]. Here important special cases

*Corresponding author.

E-mail: attaev.anatoly@yandex.ru

of the same problem were investigated, namely, the problem of complete oscillation excitation and damping. The boundary control problem for equation (1) for $\lambda = 0$ with various nonlocal, including integral form conditions, were studied in [8–12].

A number of specific formulations for distributed control problems, with oscillatory nature of the movement, are described in detail in the monograph [13], and moreover various solution methods are proposed. For example, the damping fluid flow pulsation problem in automated long main pipelines design and pipeline irrigation systems [14], [15]. As earliest works devoted to the study of boundary control problems (1) at $\lambda = 0$ the works [16–18] are worth mentioning.

There are following main results in the work:

1. Necessary and sufficient conditions are established for the functions $\varphi_0(x)$, $\psi_0(x)$, $\varphi_1(x)$, $\psi_1(x)$, which ensure the existence of the desired boundary values.

$$\psi_0(l) + \varphi'_0(l) - \psi_1(0) - \varphi'_1(0) = 0, \tag{5}$$

$$\psi_0(0) - \varphi'_0(0) - \psi_1(l) + \varphi'_1(l) = 0, \tag{6}$$

$$\lambda [\psi_0(l) + \varphi'_0(l) + \psi_1(0) + \varphi'_1(0)] = 0, \tag{7}$$

$$\varphi''_0(l) + \psi'_0(l) - \varphi''_1(0) - \psi'_1(0) = 0, \tag{8}$$

$$\varphi''_0(0) - \psi'_0(0) - \varphi''_1(l) + \psi'_1(l) = 0, \tag{9}$$

$$\begin{aligned} & \varphi_0(0) - \varphi_1(l) + [\varphi_0(l) - \varphi_1(0)] e^{\frac{\lambda l^2}{8}} + \\ & + \frac{1}{2} \int_0^l e^{\frac{\lambda t^2}{8}} [\psi_0(t) - \psi_1(l-t)] dt - \frac{\lambda}{4} \int_0^l t e^{\frac{\lambda t^2}{8}} [\varphi_0(t) - \varphi_1(l-t)] dt = 0. \end{aligned} \tag{10}$$

2. Under conditions (5)–(10), an explicit analytical form of the sought boundary controls is found

$$\mu(t) = \varphi_1(l-t) + F_1(t, \lambda) - \frac{\lambda}{4} t F_2(t, \lambda), \tag{11}$$

$$\nu(t) = \varphi_0(l-t) + F_1(l-t, \lambda) - \frac{\lambda}{4} t F_2(l-t, \lambda), \tag{12}$$

where

$$\begin{aligned} F_1(t, \lambda) = & \frac{1}{2} e^{-\frac{\lambda t^2}{8}} [\varphi_0(0) - \varphi_1(l)] + \frac{1}{2} [\varphi_0(t) - \varphi_1(l-t)] - \\ & - \frac{\lambda}{8} \int_0^t \xi e^{\frac{\lambda(t^2-\xi^2)}{8}} [\varphi_0(\xi) - \varphi_1(l-\xi)] d\xi - \frac{1}{8} \int_0^t e^{\frac{\lambda(t^2-\xi^2)}{8}} [\psi_0(\xi) - \psi_1(l-\xi)] d\xi, \end{aligned}$$

$$\begin{aligned} F_2(t, \lambda) = & \sqrt{\frac{2\pi}{\lambda}} \Phi_0\left(\frac{\sqrt{\lambda}}{2} t\right) [\varphi_0(0) - \varphi_1(l)] + \\ & + \frac{1}{2} \int_0^t [\varphi_0(\xi) - \varphi_1(l-\xi)] d\xi - \\ & - \sqrt{\frac{\lambda\pi}{8}} \int_0^t \left[\Phi_0\left(\frac{\sqrt{\lambda}}{2} t\right) - \Phi_0\left(\frac{\sqrt{\lambda}}{2} \xi\right) \right] \xi e^{\frac{\lambda\xi^2}{8}} [\varphi_0(\xi) - \varphi_1(l-\xi)] d\xi + \end{aligned}$$

$$+\sqrt{\frac{2\pi}{\lambda}} \int_0^t \left[\Phi_0\left(\frac{\sqrt{\lambda}}{2}t\right) - \Phi_0\left(\frac{\sqrt{\lambda}}{2}\xi\right) \right] e^{\frac{\lambda\xi^2}{8}} [\psi_0(\xi) - \psi_1(l-\xi)] d\xi,$$

where $\Phi_0(x) = \frac{1}{\sqrt{2\pi}} \int_0^x e^{-\frac{\xi^2}{2}} d\xi$ is the distribution function for normalizing and centering processes.

1 Main part

1.1 An analogue of the d'Alembert formula

Using the characteristic variables $\xi = x - t$, $\eta = x + t$ equation (1) is written out as

$$v_{\xi\eta} = \frac{\lambda}{4} v(0, \eta), \quad (13)$$

where $v(\xi, \eta) = u\left(\frac{\xi+\eta}{2}, \frac{\eta-\xi}{2}\right)$.

Any solution to equation (13) is a solution to the following loaded integral equation.

$$v(\xi, \eta) - \frac{\lambda}{4} \xi \int_a^\eta v(0, t) dt = f(\xi) + g(\eta), \quad (14)$$

where $f(\xi)$ and $g(\eta)$ are arbitrary twice continuously differentiable functions. Since for $\xi = 0$ by (14) it follows that $v(0, \eta) = f(0) + g(\eta)$, then solution (14) takes the form

$$v(\xi, \eta) = f(\xi) + g(\eta) + \frac{\lambda}{4} \xi \int_a^\eta [f(0) + g(t)] dt.$$

Replacing $P(\eta) = \int_a^\eta [f(0) + g(t)] dt$ in the last formula and then renaming $P(\eta)$ by $g(\eta)$, we obtain

$$v(\xi, \eta) = f(\xi) - f(0) + g'(\eta) + \frac{\lambda}{4} \xi g(\eta).$$

Or when using the old coordinates, get

$$u(x, t) = f(x-t) - f(0) + g'(x+t) + \frac{\lambda}{4} (x-t) g(x+t). \quad (15)$$

We call formula (15) an analogue of the d'Alembert formula for equation (1).

Formula (15) below is more convenient for further use. It should be noted that in (15) the functions $f(t)$ and $g'(t)$ are twice continuously differentiable.

1.2 Searching algorithm for $\mu(t)$ and $\nu(t)$

Before searching for boundary controls, let us remember that when $\lambda = 0$ the minimum time t required for the desired control is uniquely equal to l . As noted in [12], this time is determined by the characteristics of the initial equation that simulates the oscillation process. From a mathematical point of view, problem (2), (4) for equation (1) with $\lambda = 0$ in the rectangle $(0, l) \times (0, T)$ has a unique solution if and only if $T = l$. If $T < l$, the problem is overdetermined, $T > l$, the problem is underdetermined. In our case when $\lambda \neq 0$ the equation commands the condition $T = l$. This is due to the fact that for any arbitrary point $(x, t) \in (0, l) \times (0, T)$, belonging to the point $(\frac{x+t}{2}, \frac{x-t}{2}) \in (0, l) \times (0, T)$ is possible if and only if $T = l$. Therefore, further we assume that $T = l$.

We introduce the following equation for the functions $f(x)$ and $g(x)$ in formula (15).

$$f(x) = \begin{cases} f_0(x), & x \in [0, l], \\ f_1(x), & x \in [-l, 0], \end{cases} \quad (16)$$

$$g(x) = \begin{cases} g_0(x), & x \in [0, l], \\ g_1(x), & x \in [l, 2l]. \end{cases} \quad (17)$$

We call the function $u(x, t) \in C^1(\bar{\Omega}) \cap C^2(\Omega)$ a regular solution to equation (1) where $\Omega = (0, l) \times (0, l)$.

Letting (15) satisfy (3) and taking into account (16), (17), we obtain

$$\mu(t) = f_1(-t) - f_0(0) + g'_0(t) - \frac{\lambda}{4} t g_0(t), \quad t \in [0, l], \quad (18)$$

$$\nu(t) = f_0(l-t) - f_0(0) + g'_0(l+t) + \frac{\lambda}{4} (l-t) g_0(l+t), \quad t \in [0, l]. \quad (19)$$

Letting (15) satisfy (2) and (4) for $T = l$ we obtain

$$f_0(x) - f_0(0) + g'_0(x) + \frac{\lambda}{4} x g_0(x) = \varphi_0(x), \quad (20)$$

$$-f'_0(x) + g''_0(x) - \frac{\lambda}{4} g_0(x) + \frac{\lambda}{4} x g'_0(x) = \psi_0(x), \quad (21)$$

$$f_1(x-l) - f_0(0) + g'_1(x+l) + \frac{\lambda}{4} (x-l) g_1(x+l) = \varphi_1(x), \quad (22)$$

$$-f'_1(x-l) + g''_1(x+l) - \frac{\lambda}{4} g_1(x+l) + \frac{\lambda}{4} (x-l) g'_1(x+l) = \psi_1(x), \quad (23)$$

where $x \in [0, l]$.

Differentiating (20), (22), subtracting and adding term by term with (21), (23), respectively, obtain

$$f'_0(x) + \frac{\lambda}{4} g_0(x) = \frac{1}{2} \varphi'_0(x) - \frac{1}{2} \psi_0(x),$$

$$g''_0(x) + \frac{\lambda}{4} x g'_0(x) = \frac{1}{2} \varphi'_0(x) + \frac{1}{2} \psi_0(x), \quad (24)$$

$$f'_1(x-l) + \frac{\lambda}{4} g_1(x+l) = \frac{1}{2} \varphi'_1(x) - \frac{1}{2} \psi_1(x),$$

$$g''_1(x+l) + \frac{\lambda}{4} (x-l) g'_1(x+l) = \frac{1}{2} \varphi'_1(x) + \frac{1}{2} \psi_1(x). \quad (25)$$

Employing the second equation of (24) we obtain

$$\left[g'_0(x) e^{\frac{\lambda x^2}{8}} \right]' = \frac{1}{2} e^{\frac{\lambda x^2}{8}} [\varphi'_0(x) + \psi_0(x)],$$

$$g'_0(x) = g'_0(0) e^{-\frac{\lambda x^2}{8}} + \frac{1}{2} e^{-\frac{\lambda x^2}{8}} \int_0^x e^{\frac{\lambda t^2}{8}} \varphi'_0(t) dt + \frac{1}{2} e^{-\frac{\lambda x^2}{8}} \int_0^x e^{\frac{\lambda t^2}{8}} \psi_0(t) dt.$$

Using integration by parts for the first integral and taking into account that $g'_0(0) = \varphi_0(0)$, obtain

$$g'_0(x) = \frac{1}{2} \varphi_0(0) e^{-\frac{\lambda x^2}{8}} + \frac{1}{2} \varphi_0(x) - \frac{\lambda}{8} e^{-\frac{\lambda x^2}{8}} \int_0^x t e^{\frac{\lambda t^2}{8}} \varphi_0(t) dt + \frac{1}{2} e^{-\frac{\lambda x^2}{8}} \int_0^x e^{\frac{\lambda t^2}{8}} \psi_0(t) dt. \quad (26)$$

Hence

$$g_0(x) = g_0(0) + \frac{1}{2} \varphi_0(0) \int_0^x t e^{-\frac{\lambda t^2}{8}} dt + \frac{1}{2} \int_0^x \varphi_0(t) dt -$$

$$-\frac{\lambda}{8} \int_0^x e^{-\frac{\lambda \xi^2}{8}} \int_0^\xi t e^{\frac{\lambda t^2}{8}} \varphi_0(t) dt d\xi + \frac{1}{2} \int_0^x e^{-\frac{\lambda \xi^2}{8}} \int_0^\xi e^{\frac{\lambda t^2}{8}} \psi_0(t) dt d\xi.$$

Changing the order of integration in the last two integrals, get

$$\begin{aligned} g_0(x) &= g_0(0) + \sqrt{\frac{2\pi}{\lambda}} \varphi_0(0) \Phi_0\left(\frac{\sqrt{\lambda}}{2} x\right) + \frac{1}{2} \int_0^x \varphi_0(t) dt - \\ &- \sqrt{\frac{\lambda\pi}{8}} \int_0^x \left[\Phi_0\left(\frac{\sqrt{\lambda}}{2} x\right) - \Phi_0\left(\frac{\sqrt{\lambda}}{2} t\right) \right] t e^{\frac{\lambda t^2}{8}} \varphi_0(t) dt + \\ &+ \sqrt{\frac{2\pi}{\lambda}} \int_0^x \left[\Phi_0\left(\frac{\sqrt{\lambda}}{2} x\right) - \Phi_0\left(\frac{\sqrt{\lambda}}{2} t\right) \right] e^{\frac{\lambda t^2}{8}} \psi_0(t) dt. \end{aligned} \quad (27)$$

By (20) we have

$$\begin{aligned} f_0(x) &= \varphi_0(x) - g'_0(x) - \frac{\lambda}{4} x g_0(x) + f_0(0), \\ f_0(l-t) &= \varphi_0(l-t) - g'_0(l-t) - \frac{\lambda}{4} (l-t) g_0(l-t) + f_0(0). \end{aligned} \quad (28)$$

Employing the second relation of (25) we obtain

$$\begin{aligned} \left(g'_1(x+l) e^{\frac{\lambda(x-l)^2}{8}} \right)' &= \frac{1}{2} e^{\frac{\lambda}{8}(x-l)^2} \varphi'_1(x) + \frac{1}{2} e^{\frac{\lambda}{8}(x-l)^2} \psi_1(x), \\ g'_1(x+l) &= g'_1(2l) e^{\frac{\lambda}{8}(x-l)^2} + \frac{1}{2} e^{\frac{\lambda}{8}(x-l)^2} \int_l^x e^{\frac{\lambda}{8}(t-l)^2} \varphi'_1(t) dt + \frac{1}{2} e^{-\frac{\lambda}{8}(x-l)} \int_l^x e^{\frac{\lambda}{8}(x-l)^2} \psi_1(t) dt. \end{aligned}$$

Taking into account $g'_1(2l) = \varphi_1(l)$, integrating by parts the first integral, substituting x by $l-x$ and then substituting in both integrals $t = l-t$ get

$$\begin{aligned} g'_1(2l-x) &= \frac{1}{2} \varphi_1(l) e^{-\frac{\lambda x^2}{8}} + \frac{1}{2} \varphi_1(l-x) + \frac{\lambda}{8} e^{-\frac{\lambda x^2}{8}} \int_0^x t e^{-\frac{\lambda t^2}{8}} \varphi_1(l-t) dt + \\ &+ \frac{1}{2} e^{-\frac{\lambda x^2}{8}} \int_0^x t e^{-\frac{\lambda t^2}{8}} \psi_1(l-t) dt. \end{aligned} \quad (29)$$

Hence

$$\begin{aligned} g_1(2l-x) &= g_1(2l) + \frac{1}{2} \varphi_1(l) \int_0^x e^{-\frac{\lambda t^2}{8}} dt + \frac{1}{2} \int_0^x \varphi_1(l-t) dt - \\ &- \frac{\lambda}{8} \int_0^x e^{-\frac{\lambda \xi^2}{8}} \int_0^\xi t e^{\frac{\lambda t^2}{8}} \varphi_1(l-t) dt d\xi + \frac{1}{2} \int_0^x e^{-\frac{\lambda \xi^2}{8}} \int_0^\xi e^{\frac{\lambda t^2}{8}} \psi_1(l-t) dt d\xi. \end{aligned}$$

Changing the integration order in the last two integrals we get

$$\begin{aligned} g_1(2l-x) &= g_1(2l) + \sqrt{\frac{2\pi}{\lambda}} \varphi_1(l) \Phi_0\left(\frac{\sqrt{\lambda}}{2} x\right) + \frac{1}{2} \int_0^x \varphi_1(l-t) dt - \\ &- \sqrt{\frac{\lambda\pi}{8}} \int_0^x \left[\Phi_0\left(\frac{\sqrt{\lambda}}{2} x\right) - \Phi_0\left(\frac{\sqrt{\lambda}}{2} t\right) \right] t e^{\frac{\lambda t^2}{8}} \varphi_1(l-t) dt + \\ &+ \sqrt{\frac{2\pi}{\lambda}} \int_0^x \left[\Phi_0\left(\frac{\sqrt{\lambda}}{2} x\right) - \Phi_0\left(\frac{\sqrt{\lambda}}{2} t\right) \right] e^{-\frac{\lambda t^2}{8}} \psi_1(l-t) dt. \end{aligned} \quad (30)$$

By (22) we have

$$f_1(x-l) = \varphi_1(x) + f_0(0) - g'_1(x+l) - \frac{\lambda}{4}(x-l)g_1(x+l)$$

or

$$f_1(-t) = \varphi_1(l-t) + f_0(0) - g'_1(2l-t) + \frac{\lambda}{4}t g_1(2l-t). \quad (31)$$

Substituting $f_1(-t)$ by (31) into (18), and $f_0(l-t)$ by (28) into (19), we obtain

$$\mu(t) = \varphi_1(l-t) + g'_0(t) - g'_1(2l-t) - \frac{\lambda}{4}t [g_0(t) - g_1(2l-t)], \quad (32)$$

$$\nu(t) = \varphi_0(l-t) - [g'_0(l-t) - g'_1(l+t)] - \frac{\lambda}{4}(l-t) [g_0(l-t) - g_1(l+t)]. \quad (33)$$

Substituting $g'_0(t)$, $g_0(t)$, $g'_1(2l-t)$, $g_1(2l-t)$ calculated by (26), (27), (29), (30) into formulas (32), (33), and taking into account, due to the assumed continuity of $f'(x)$, that

$$\frac{\lambda}{2} [g_0(0) - g_1(2l)] = \varphi'_0 - \psi_0(0) - \varphi'_1(l) + \psi_0(l)$$

obtain the sought result (11), (12).

In order for the solution to be regular, sufficient conditions must be satisfied that ensure the existence of a boundary control. It is therefore only natural these conditions provide the functions $f(x)$ and $g(x)$ with required smoothness determined by rule (16), (17) respectively, and by the initial and boundary conditions

$$f_0(0) = f_1(0), \quad f'_0(0) = f'_1(0), \quad f''_0(0) = f''_1(0),$$

$$g_0(l) = g_1(l), \quad g'_0(l) = g'_1(l), \quad g''_0(l) = g''_1(l), \quad g'''_0(l) = g'''_1(l),$$

$$\mu(0) = \varphi_0(0), \quad \mu(l) = \varphi_1(0), \quad \nu(0) = \varphi_0(l), \quad \nu(l) = \varphi_1(l),$$

$$\mu'(0) = \psi_0(0), \quad \mu'(l) = \psi_1(0), \quad \nu'(0) = \psi_0(l), \quad \nu'(l) = \psi_1(l).$$

Satisfying the expression for the function $f_0(x)$, $f_1(x)$, $g_0(x)$, $g_1(x)$, $\mu(x)$, $\nu(x)$ represented by formulas (28), (31), (27), (30), (32), (33) according to the conditions above and after some simple transformations obtain (5)–(10). It should be noted that for $\lambda = 0$ the obtained results in this work coincide with the results obtained in [7].

References

- 1 Нахушев А.М. О задаче Дарбу для одного вырождающегося нагруженного интегро-дифференциального уравнения второго порядка / А.М. Нахушев // Дифференц. уравнения. — 1976. — 12. — № 1. — С. 103–108.
- 2 Дженалиев М.Т. Нагруженные уравнения как возмущения дифференциальных уравнений / М.Т. Дженалиев, М.И. Рамазанов. — Алматы: Ғылым, 2010. — 334 с.
- 3 Аттаев А.Х. Задача граничного управления для существенно нагруженного уравнения колебания струны / А.Х. Аттаев // Докл. Адыгской (Черкесской) Междунар. акад. наук. — 2011. — 13. — № 1. — С. 30–35.

- 4 Attaev A.Kh. Задача граничного управления для нагруженного уравнения колебания струны / А.Х. Аттаев // Дифференц. уравнения. — 2020. — 56. — № 5. — С. 646–651.
- 5 Хубиев К.У. О задаче Коши для одного нагруженного волнового уравнения / К.У. Хубиев // Докл. Адыгской (Черкесской) Междунар. акад. наук. — 2020. — 20. — № 4. — С. 9–13.
- 6 Khubiev K.U. Analogue of Tricomi problem for characteristically loaded hyperbolic-parabolic equation with variable coefficients / K.U. Khubiev // Ufa Mathematical Journal. — 2017. — 9. — No. 2. — P. 92–101.
- 7 Ильин В.А. Волновое уравнение с граничным управлением на двух концах и о полном успокоении колебательного процесса / В.А. Ильин, В.В. Тихомиров // Дифференц. уравнения. — 1999. — 35. — № 5. — С. 692–704.
- 8 Ильин В.А. Граничное управление смещением на одном конце струны при наличии нелокального граничного условия одного из четырех типов и его оптимизация / В.А. Ильин // Дифференц. уравнения. — 2008. — 44. — № 11. — С. 1487–1498.
- 9 Моисеев Е.И. Оптимальное граничное управление смещенными колебаниями струны с нелокальным условием нечетности первого рода / Е.И. Моисеев, А.А. Холмеева // Дифференц. уравнения. — 2010. — 46. — № 11. — С. 1623–1630.
- 10 Моисеев Е.И. Оптимальное граничное управление смещенными колебаниями струны с нелокальным условием четности второго рода / Е.И. Моисеев, А.А. Холмеева // Дифференц. уравнения. — 2011. — 47. — № 1. — С. 127–134.
- 11 Attaev A.Kh. Boundary control by displacement at one end of string and the integral condition on the other / A.Kh. Attaev // Int. Conf. "Functional Analysis in Interdisciplinary Applications" (FAIA 2017), Melville, New York: Am. Inst. Phys. — 2017. — P. 040005.
- 12 Attaev A.Kh. On Problem of Internal Boundary Control for String Vibration Equation / A.Kh. Attaev // Bulletin of the Karaganda University. Mathematics series. — 2021. — 1. — No. 101. — P. 4–10.
- 13 Бутковский А.Г. Методы управления системами с распределенными параметрами / А.Г. Бутковский — М.: Наука, 1975. — 568 с.
- 14 Байрактаров Б.Р. Оптимизация гидравлических систем с переменными параметрами / Б.Р. Байрактаров // Мат. моделирование. — 1998. — 10. — № 2. — С. 41–47.
- 15 Bayraktar B. Determining optimum hydraulic parameters in branched water supply system / B. Bayraktar // Journal of the Balkan Tribological Association. — 2012. — 18. — No. 2. — P. 174–183.
- 16 Бутковский А.Г. Оптимальное управление двумерной колебательной системой / А.Г. Бутковский, Л.И. Полтавский // Автоматика и телемеханика. — 1966. — № 4. — С. 32–41.
- 17 Lions J.L. Exact controllability, stabilization, and perturbations for distributed systems / J.L. Lions // SIAM Rev. — 1988. — 30. — No. 2. — P. 1–68.
- 18 Васильев Ф.П. О двойственности в линейных задачах управления и наблюдения / Ф.П. Васильев // Дифференц. уравнения. — 1995. — 31. — № 11. — С. 1893–1900.

А.Х. Аттаев

РҒА КБҒО Қолданбалы математика және автоматтандыру институты, Нальчик, Ресей

Гиперболалық теңдеу үшін оның сипаттамаларының бірі бойынша жүктелген шекаралық бақылау есебі

Мақалада регулярлы шешім тұрғысынан бір өлшемді жолдың тербеліс теңдеуі үшін сипаттамаларының бірі бойынша жүктелген шекаралық бақылау есебінің бірегей шешімі зерттелген. Шешу әдісі осы теңдеу үшін құрылған Даламбер формуласының аналогына негізделген. Ұзындығы бірдей кесінділер бойынша бастапқы және соңғы Коши деректері берілгенде бұл теңдеудің шешімінің анықталу облысы квадрат болатыны атап өтілген. Квадраттың қабырғасы берілген кесіндінің ұзындығына тең. Шекаралық бақылаудың өзі Даламбер формуласының аналогының құрамдас бөліктері бойынша анықталған, олар өз кезегінде Кошидің бастапқы және соңғы деректері бойынша бірегей түрде анықталады. Ізделінді шекаралық бақылауларға арналған соңғы формулаларда нормаланған және орталықтандырылған үлестірімдердің таралу функциясы қатысатынын атап өткен жөн, бұл жалпы айтқанда гиперболалық типті теңдеулермен басталатын бастапқы және шекаралық есептер үшін тән емес.

Кілт сөздер: гиперболалық теңдеу, таралған тербелмелі жүйе, газ немесе сұйық ағындарының пульсациясын бәсеңдету есебі, жүктелген теңдеу, бастапқы шарттар, шекаралық шарттар, Даламбер формуласының аналогы, шекаралық бақылау, қалыпты үлестірім, үлестірім функциясы.

А.Х. Аттаев

Институт прикладной математики и автоматизации КБНЦ РАН, Нальчик, Россия

Задача граничного управления для нагруженного вдоль одной из своих характеристик гиперболического уравнения

В статье исследована однозначная разрешимость задачи граничного управления для нагруженного вдоль одной из своих характеристик одномерного уравнения колебания струны в терминах регулярного решения. Метод решения основан на аналоге формулы Даламбера, построенного для данного уравнения. Отмечено, что областью определения решения данного уравнения, когда начальные и финальные данные Коши задаются на отрезках одинаковой длины, является квадрат. Сторона квадрата равна длине данного отрезка. Сами граничные управления определены через компоненты аналога формулы Даламбера, которые, в свою очередь, однозначно определяются через начальные и финальные данные Коши. Следует отметить, что в окончательных формулах для искомых граничных управлений участвует функция распределения нормированного и центрированного распределения, что, вообще говоря, не характерно для начальных и граничных задач инициированных уравнениями гиперболического типа.

Ключевые слова: гиперболическое уравнение, распределённая колебательная система, задача гашения пульсации потоков газа или жидкости, нагруженное уравнение, начальные условия, граничные условия, аналог формулы Даламбера, граничные управления, нормальное распределение, функция распределения.

References

- 1 Nakhushiev, A.M. (1976). O zadache Darbu dlia odnogo vyrozhdaiushchegosia nagruzhenno integro-differentsialnogo uravneniia vtorogo poriadka [On the Darboux problem for a degenerate loaded integro-differential equation of the second order]. *Differentsialnye uravneniia — Differ. Equations*, 12(1), 103–108 [in Russian].

- 2 Dzhenaliev, M.T., & Ramazanov, M.I. (2010). *Nagruzhennye uravneniia kak vozmushcheniia differentsialnykh uravnenii* [Loaded equations as perturbations of differential equations]. Almaty: Gylym [in Russian].
- 3 Attaev, A.Kh. (2011). Zadacha granichnogo upravleniia dlia sushchestvenno nagruzhennogo uravneniia kolebaniia struny [Boundary control problem for essentially loaded string vibration equation]. *Doklady Adygskoi (Cherkesskoi) Mezhdunarodnoi akademii nauk — Reports of Adyghe (Circassian) International Academy of Sciences*, 13 (1), 30–35 [in Russian].
- 4 Attaev, A.Kh. (2020). Zadacha granichnogo upravleniia dlia nagruzhennogo uravneniia kolebaniia struny [Boundary control problem for a loaded wave equation]. *Differentsialnye uravneniia — Differ. Equations*, 56(5), 646–651 [in Russian].
- 5 Khubiev, K.U. (2020). O zadache Koshi dlia odnogo nagruzhennogo volnovogo uravneniia [On the Cauchy problem for one-loaded wave equation]. *Doklady Adygskoi (Cherkesskoi) Mezhdunarodnoi akademii nauk — Reports of Adyghe (Circassian) International Academy of Sciences*, 20(4), 9–13 [in Russian].
- 6 Khubiev, K.U. (2017). Analogue of Tricomi problem for characteristically loaded hyperbolic-parabolic equation with variable coefficients. *Ufa Mathematical Journal*, 9(2), 92–101.
- 7 Ilin, V.A., & Tikhomirov, V.V. (1999). Volnoe uravnenie s granichnym upravleniem na dvukh kontsakh i o polnom uspokoenii kolebatelnogo protsessa [The wave equation with boundary control at two ends and the problem of the complete oscillation damping]. *Differentsialnye uravneniia — Differ. Equations*, 35(5), 692–704 [in Russian].
- 8 Ilin, V.A. (2008). Granichnoe upravlenie smeshcheniem na odnom kontse struny pri nalichii nelokalnogo granichnogo usloviia odnogo iz chetyrekh tipov i ego optimizatsiia [Boundary control by displacement at one end of a string in the presence of a nonlocal boundary condition of one of four types and its optimization]. *Differentsialnye uravneniia — Differ. Equations*, 44(11), 1487–1498 [in Russian].
- 9 Moiseev, E.I., & Kholomeeva, A.A. (2010). Optimalnoe granichnoe upravlenie smeshchennymi kolebaniiami struny s nelokalnym uslovie nechetnosti pervogo roda [Optimal boundary displacement control of string vibrations with a nonlocal oddness condition of the first kind]. *Differentsialnye uravneniia — Differ. Equations*, 46(11), 1623–1630 [in Russian].
- 10 Moiseev, E.I., & Kholomeeva, A.A. (2011). Optimalnoe granichnoe upravlenie smeshchennymi kolebaniiami struny s nelokalnym uslovie chetnosti vtorogo roda [Optimal boundary displacement control of string vibrations with a nonlocal evenness condition of the second kind]. *Differentsialnye uravneniia — Differ. Equations*, 47(1), 127–134 [in Russian].
- 11 Attaev, A.Kh. (2017). Boundary control by displacement at one end of string and the integral condition on the other. Int. Conf. "Analysis in Interdisciplinary Applications" (FAIA 2017), Melville, New York: Am. Inst. Phys., 040005.
- 12 Attaev, A.Kh. (2021). On Problem of Internal Boundary Control for String Vibration Equation. *Bulletin of the Karaganda University. Mathematics series*, 1(101), 4–10.
- 13 Butkovskii, A.G. (1975). *Metody upravleniia sistemami s raspredelennymi parametrami* [Methods of control systems with distributed parameters]. Moscow: Nauka [in Russian].
- 14 Bayraktarov, B.R. (1998). Optimizatsiia gidravlicheskikh sistem s peremennymi parametrami [Optimization of hydraulic systems with variable parameters]. *Matematicheskoe modelirovanie — Mathematical Models and Computer Experiment*, 41–47 [in Russian].
- 15 Bayraktar, B. (2012). Determining optimum hydraulic parameters in branched water supply system. *Journal of the Balkan Tribological Association*, 18(2), 174–183.

- 16 Butkovskiy, A.G., & Poltavskiy, L.I. (1966). Optimalnoe upravlenie dvumernoi kolebatelnoi sistemoi [Optimal control over a two-dimensional vibrational system]. *Avtomatika i telemekhanika – Automation and Remote Control*, 4, 32–41 [in Russian].
- 17 Lions, J.L. (1988). Exact controllability, stabilization, and perturbations for distributed systems. *SIAM Rev*, 30(2), 1–68.
- 18 Vasilev, F.P. (1995). O dvoistvennosti v lineinykh zadachakh upravleniia i nabludeniia [On duality in linear control and observation problems]. *Differentsialnye uravneniia – Differ. Equations*, 31(11), 1893–1900 [in Russian].

Buketov University